

AS/AC - CE

 : -10°÷+99°C


Mod	Cod		P _{PRE}	P _{MAX}						
AC-2 *	A012J07	2	1,5	8	+99°C	130	230	-	3/4"	150 x 150 x 240
AC 5 *	A012J11	5	1,5	8	+99°C	205	240	-	3/4"	210 x 210 x 250
AC 8 CE	A012J16	8	1,5	8	+99°C	205	315	-	3/4"	210 x 210 x 320
AC 18 CE	A012J24	18	1,5	8	+99°C	270	430	-	3/4" - 1"	280 x 280 x 450
AC 20 PN25 CE	A012T25	20	5	25	+50°C	270	485	-	3/4" - 1"	280 x 280 x 500
AC 25 CE	A012J27	24	1,5	8	+99°C	270	470	-	3/4" - 1"	280 x 280 x 470
AFV 24 CE	A032R27	24	1,5	16	+99°C	270	470	-	3/4" - 1"	280 x 280 x 470
AC 25 GPM CE	A022J27	24	1,5	8	+99°C	270	290	470	3/4" - 1"	280 x 300 x 470
AS 25 CE	A002J27	24	1,5	8	+99°C	360	365	-	3/4" - 1"	360 x 360 x 380

* ESENTE DA MARCATURA CE

